

4900 Adjus Table Wrench

• A smaller angle (15°) wrench aligns the wrench with the nut in a manner that offers speed, precision, ergonomic comfort and provides greater leverage distance thus reducing hand & arm fatigue. It makes the hardest work easy.

• Compared to 22.5° wrench, a swing angle of 15° is more suitable for operation in limited working area.



Size inch(mm)	Standard Jaw Opening Width(mm)	Our Wider Max. Jaw Opening Not Less Than(mm)	Using Range for	
			Metric Hexagon Nuts Size	SAE Hexagon Nuts Size
4 (100)	13	17	M1-M10	W1/8-W3/8
6 (150)	20	22.9	M1-M16	W1/8-W1/2
8 (200)	24	28.6	M1-M18	W1/8-W5/8
10 (250)	29	32.8	M1-M22	W1/8-W3/4
12 (300)	34	38.1	M1-M24	W1/8-W7/8
15 (375)	43	50	M1-M33	W1/8-W1-1/4
18 (450)	53	60	M1-M39	W1/8-W1-1/2
24 (600)	62	70	M1-M45	W1/8-W1-3/4

4901 Wrench



C: Chrom
M: Matt
P: Black

Item No.	Size (mm)	L (mm)	W (g)
4901(C,M,P)-0404	17	100	55
4901(C,M,P)-0606	23.9	150	120
4901(C,M,P)-0808	28.6	200	240
4901(C,M,P)-1010	32.8	250	400
4901(C,M,P)-1212	38.1	300	650
4901(C,M,P)-1515	50.0	375	1188
4901(C,M,P)-1818	60.0	450	1870
4901(C,M,P)-2424	70.0	600	3040

4902 Slipage-Reduce Type



Item No.	Size (mm)	L (mm)	W (g)
4902C-0404	17	110	60
4902C-0606	23.9	160	122
4902C-0808	28.6	210	240
4902C-1010	32.8	260	400
4902C-1212	38.1	310	605
4902C-1515	51.0	390	1140

GET A GRIP ON FASTENER DAMAGE

INNOVATION OF:
• FORM
• FUNCTION AND
• FITNESS FOR DUTY

